



Precision Monolithic Quad SPST CMOS Analog Switches

DESCRIPTION

The DG417B, DG418B, DG419B monolithic CMOS analog switches were designed to provide high performance switching of analog signals. Combining low power, low leakages, high speed, low on-resistance and small physical size, the DG417B series is ideally suited for portable and battery powered industrial and military applications requiring high performance and efficient use of board space. To achieve high-voltage ratings and superior switching performance, the DG417B series is built on Vishay Siliconix's high voltage silicon gate (HVSG) process. Break-before-make is guaranteed for the DG419B, which is an SPDT configuration. An epitaxial layer prevents latchup. Each switch conducts equally well in both directions when on, and blocks up to the power supply level when off. The DG417B and DG418B respond to opposite control logic levels as shown in the Truth Table.

BENEFITS

- Widest dynamic range
- Low signal errors and distortion
- Break-before-make switching action
- Simple interfacing
- Reduced board space
- Improved reliability

FEATURES

- ± 15 V analog signal range
- On-resistance - $R_{DS(on)}$: 15 Ω
- Fast switching action - t_{on} : 110 ns
- TTL and CMOS compatible
- MSOP-8 and SOIC-8 package





Note

* This datasheet provides information about parts that are RoHS-compliant and / or parts that are non RoHS-compliant. For example, parts with lead (Pb) terminations are not RoHS-compliant. Please see the information / tables in this datasheet for details

APPLICATIONS

- Precision test equipment
- Precision instrumentation
- Battery powered systems
- Sample-and-hold circuits
- Military radios
- Guidance and control systems
- Hard disk drivers

FUNCTIONAL BLOCK DIAGRAM AND PIN CONFIGURATION



TRUTH TABLE		
LOGIC	DG417B	DG418B
0	On	Off
1	Off	On

Note

- Logic "0" ≤ 0.8 V
- Logic "1" ≥ 2.4 V

TRUTH TABLE (DG419B)		
LOGIC	SW ₁	SW ₂
0	On	Off
1	Off	On

Note

- Logic "0" ≤ 0.8 V
- Logic "1" ≥ 2.4 V




ORDERING INFORMATION		
TEMP. RANGE	PACKAGE	PART NUMBER
DG417B, DG418B		
-40 °C to +85 °C	8-pin narrow SOIC	DG417BDY-E3 DG417BDY-T1-E3
		DG418BDY-E3 DG418BDY-T1-E3
	8-pin MSOP	DG417BDQ-T1-E3
		DG418BDQ-T1-E3
DG419B		
-40 °C to +85 °C	8-pin narrow SOIC	DG419BDY-E3 DG419BDY-T1-E3
	8-pin MSOP	DG419BDQ-T1-E3

ABSOLUTE MAXIMUM RATINGS (T _A = 25 °C, unless otherwise noted)			
PARAMETER	LIMIT	UNIT	
V-	-20	V	
V+	20		
GND	25		
V _L	(GND - 0.3) to (V+) + 0.3		
Digital inputs ^a , V _S , V _D	(V-) - 2 to (V+) + 2 or 30 mA, whichever occurs first		
Current (any terminal) continuous	30	mA	
Current (S or D) pulsed at 1 ms, 10 % duty cycle	100		
Storage temperature	-65 to +150	°C	
Power dissipation (package) ^b	8-pin narrow SOIC ^d	400	mW
	8-pin MSOP ^e	400	
	8-pin CerDIP ^e	600	

Notes

- a. Signals on S_x, D_x, or IN_x exceeding V+ or V- will be clamped by internal diodes. Limit forward diode current to maximum current ratings
- b. All leads welded or soldered to PC board
- c. Derate 5.3 mW/°C above 75 °C
- d. Derate 4 mW/°C above 70 °C
- e. Derate 8 mW/°C above 75 °C

SCHEMATIC DIAGRAM (Typical Channel)

Fig. 1



SPECIFICATIONS ^a											
PARAMETER	SYMBOL	TEST CONDITIONS UNLESS OTHERWISE SPECIFIED $V_+ = 15\text{ V}$, $V_- = -15\text{ V}$, $V_L = 5\text{ V}$, $V_{IN} = 2.4\text{ V}$, 0.8 V^f		TEMP. ^b	TYP. ^c	A SUFFIX -55 °C to +125 °C		D SUFFIX -40 °C to +85 °C		UNIT	
						MIN. ^d	MAX. ^d	MIN. ^d	MAX. ^d		
Analog Switch											
Analog signal range ^e	V_{ANALOG}			Full	-	-15	15	-15	15	V	
Drain-source on-resistance	$R_{DS(on)}$	$I_S = -10\text{ mA}$, $V_D = \pm 12.5\text{ V}$, $V_+ = 13.5\text{ V}$, $V_- = -13.5\text{ V}$		Room	15	-	25	-	25	Ω	
				Full	-	-	34	-	29		
Switch off leakage current	$I_{S(off)}$	$V_+ = 16.5\text{ V}$, $V_- = -16.5\text{ V}$ $V_D = \pm 15.5\text{ V}$, $V_S = \pm 15.5\text{ V}$		Room	-0.1	-0.25	0.25	-0.25	0.25	nA	
				Full	-	-20	20	-5	5		
	$I_{D(off)}$			Room	-0.1	-0.25	0.25	-0.25	0.25		
				Full	-	-20	20	-5	5		
	DG419B			Room	-0.1	-0.75	0.75	-0.75	0.75		
				Full	-	-60	60	-12	12		
Channel on leakage current	$I_{D(on)}$	$V_+ = 16.5\text{ V}$, $V_- = -16.5\text{ V}$ $V_S = V_D = \pm 15.5\text{ V}$		DG417B	Room	-0.4	-0.4	0.4	-0.4	0.4	
				DG418B	Full	-	-40	40	-10	10	
				DG419B	Room	-0.4	-0.75	0.75	-0.75	0.75	
					Full	-	-60	60	-12	12	
Digital Control											
Input current V_{IN} low	I_{IL}			Full	-	-0.5	0.5	-0.5	0.5	μA	
Input current V_{IN} high	I_{IH}			Full	-	-0.5	0.5	-0.5	0.5		
Dynamic Characteristics											
Turn-on time	t_{on}	$R_L = 300\ \Omega$, $C_L = 35\text{ pF}$, $V_S = \pm 10\text{ V}$, see Switching Time Test Circuit		DG417B	Room	62	-	89	-	89	ns
				DG418B	Full	-	-	106	-	99	
Turn-off time	t_{off}			DG417B	Room	53	-	80	-	80	
				DG418B	Full	-	-	88	-	86	
Transition time	t_{TRANS}	$R_L = 300\ \Omega$, $C_L = 35\text{ pF}$, $V_{S1} = \pm 10\text{ V}$, $V_{S2} = \pm 10\text{ V}$		DG419B	Room	60	-	87	-	87	
					Full	-	-	96	-	93	
Break-before-make time delay	t_D	$R_L = 300\ \Omega$, $C_L = 35\text{ pF}$, $V_{S1} = V_{S2} = \pm 10\text{ V}$		DG419B	Room	16	3	-	3	-	
Charge injection	Q	$C_L = 10\text{ nF}$, $V_{gen} = 0\text{ V}$, $R_{gen} = 0\ \Omega$		Room	38	-	-	-	-	pC	
Off isolation ^e	OIRR	$R_L = 50\ \Omega$, $C_L = 5\text{ pF}$, $f = 1\text{ MHz}$		Room	-82	-	-	-	-	dB	
Channel-to-channel crosstalk ^e	X_{TALK}		DG419B	Room	-88	-	-	-	-		
Source off capacitance ^e	$C_{S(off)}$	$f = 1\text{ MHz}$, $V_S = 0\text{ V}$			Room	12				pF	
Drain off capacitance ^e	$C_{D(off)}$				DG417B	Room	12				
Channel on capacitance ^e	$C_{D(on)}$				DG417B	Room	50				
		DG418B	Room	50							
DG419B					Room	57					
					Full	-	-5	-	-5	-	
Power Supplies											
Positive supply current	I_+	$V_+ = 16.5\text{ V}$, $V_- = -16.5\text{ V}$, $V_{IN} = 0\text{ V}$ or 5 V		Room	0.001	-	1	-	1	μA	
					Full	-	-	5	-		5
Negative supply current	I_-			Room	-0.001	-1	-	-1	-		
					Full	-	-5	-	-5		-
Logic supply current	I_L			Room	0.001	-	1	-	1		
					Full	-	-	5	-		5
Ground current	I_{GND}			Room	-0.001	-1	-	-1	-		
					Full	-	-5	-	-5		-



SPECIFICATIONS ^a										
PARAMETER	SYMBOL	TEST CONDITIONS UNLESS OTHERWISE SPECIFIED V ₊ = 12 V, V ₋ = 0 V, V _L = 5 V, V _{IN} = 2.4 V, 0.8 V ^f		TEMP. ^b	TYP. ^c	A SUFFIX -55 °C to +125 °C		D SUFFIX -40 °C to +85 °C		UNIT
						MIN. ^d	MAX. ^d	MIN. ^d	MAX. ^d	
Analog Switch										
Analog signal range ^e	V _{ANALOG}			Full	-	0	12	0	12	V
Drain-source on-resistance	R _{DS(on)}	I _S = -10 mA, V _D = 3.8 V, V ₊ = 10.8 V		Room	26	-	35	-	35	Ω
				Full	-	-	52	-	45	
Dynamic Characteristics										
Turn-on time	t _{on}	R _L = 300 Ω, C _L = 35 pF, V _S = 8 V, see Switching Time Test Circuit		Room	100	-	125	-	125	ns
				Full	-	-	155	-	143	
Turn-off time	t _{off}			Room	38	-	66	-	66	
				Full	-	-	73	-	69	
Break-before-make time delay	t _D	R _L = 300 Ω, C _L = 35 pF	DG419B	Room	62	25	-	25	-	
Transition time	t _{TRANS}	R _L = 300 Ω, C _L = 35 pF, V _{S1} = 0 V, 8 V, V _{S2} = 8 V, 0 V		Room	95	-	119	-	119	
				Full	-	-	153	-	141	
Charge injection	Q	C _L = 10 nF, V _{gen} = 0 V, R _{gen} = 0 Ω		Room	18	-	-	-	-	pC
Power Supplies										
Positive supply current	I ₊	V ₊ = 13.2 V, V _L = 5.25 V, V _{IN} = 0 V or 5 V		Room	0.001	-	1	-	1	μA
				Full	-	-	5	-	5	
Negative supply current	I ₋			Room	-0.001	-1	-	-1	-	
				Full	-	-5	-	-5	-	
Logic supply current	I _L			Room	0.001	-	1	-	1	
				Full	-	-	5	-	5	
Ground current	I _{GND}			Room	-0.001	-1	-	-1	-	
				Full	-	-5	-	-5	-	


Notes

- a. Refer to PROCESS OPTION FLOWCHART
- b. Room = 25 °C, full = as determined by the operating temperature suffix
- c. Typical values are for DESIGN AID ONLY, not guaranteed nor subject to production testing
- d. The algebraic convention whereby the most negative value is a minimum and the most positive a maximum, is used in this datasheet
- e. Guaranteed by design, not subject to production test
- f. V_{IN} = input voltage to perform proper function


Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.




TYPICAL CHARACTERISTICS (T_A = 25 °C, unless otherwise noted)




On-Resistance vs. V_D and Unipolar Power




On-Resistance vs. V_D and Dual Supply Voltage




On-Resistance vs. V_D and Temperature



On-Resistance vs. V_D and Temperature




Leakage vs. Analog Voltage




Supply Current vs. Input Switching Frequency




TYPICAL CHARACTERISTICS (T_A = 25 °C, unless otherwise noted)




Switching Time vs. Temperature




Transition Time vs. Temperature




Transition Time vs. Temperature



Insertion Loss, Off-Isolation Crosstalk vs. Frequency




Switching Threshold vs. Supply Voltage




Insertion Loss, Off-Isolation Crosstalk vs. Frequency




TYPICAL CHARACTERISTICS (T_A = 25 °C, unless otherwise noted)




Charge Injection vs. Analog Voltage (measured at drain pin)



Charge Injection vs. Analog Voltage (measured at source pin)





Charge Injection vs. Analog Voltage (measured at drain pin)



Charge Injection vs. Analog Voltage (measured at source pin)

TEST CIRCUITS

V_O is the steady state output with the switch on.



Note: Logic input waveform is inverted for switches that have the opposite logic sense.

Fig. 2 - Switching Time (DG417B/DG418B)

TEST CIRCUITS







Fig. 3 - Break-Before-Make (DG419B)



CL (includes fixture and stray capacitance)

$$V_O = V_S \frac{R_L}{R_L + r_{DS(on)}}$$

Fig. 4 - Transition Time (DG419B)





Fig. 5 - Charge Injection

TEST CIRCUITS




Fig. 6 - Crosstalk




Fig. 7 - Off isolation




Fig. 8 - Insertion Loss





Fig. 9 - Source/Drain Capacitances



PRODUCT SUMMARY						
Part number	DG417B	DG417B	DG418B	DG418B	DG419B	DG419B
Status code	2	2	2	2	2	2
Configuration	SPST x 1, NC	SPST x 1, NC	SPST x 1, NO	SPST x 1, NO	SPDT x 1	SPDT x 1
Single supply min. (V)	5	5	5	5	5	5
Single supply max. (V)	36	36	36	36	36	36
Dual supply min. (V)	5	5	5	5	5	5
Dual supply max. (V)	20	20	20	20	20	20
On-resistance (Ω)	15	15	15	15	15	15
Charge injection (pC)	38	38	38	38	38	38
Source on capacitance (pF)	50	50	50	50	57	57
Source off capacitance (pF)	12	12	12	12	12	12
Leakage switch on typ. (nA)	0.4	0.4	0.4	0.4	0.4	0.4
Leakage switch off max. (nA)	0.25	0.25	0.25	0.25	0.75	0.75
-3 dB bandwidth (MHz)	-	-	-	-	-	-
Package	SO-8 (narrow) AS	MSOP-8	SO-8 (narrow) AS	MSOP-8	SO-8 (narrow) AS	MSOP-8
Functional circuit / applications	Multi purpose, instrumentation, medical and healthcare	Multi purpose, instrumentation, medical and healthcare	Multi purpose, instrumentation, medical and healthcare	Multi purpose, instrumentation, medical and healthcare	Multi purpose, instrumentation, medical and healthcare	Multi purpose, instrumentation, medical and healthcare
Interface	Parallel	Parallel	Parallel	Parallel	Parallel	Parallel
Single supply operation	Yes	Yes	Yes	Yes	Yes	Yes
Dual supply operation	Yes	Yes	Yes	Yes	Yes	Yes
Turn on time max. (ns)	89	89	89	89	89	89
Crosstalk and off isolation	-88	-88	-88	-88	-88	-88

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?61566.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.