



NOTES:

- METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
- INSULATORS: PBT GF UL 94 V-0; BLACK
- CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.):
□ PLEASE ADD 1 for 30µm HARD GOLD over min. 50µm NICKEL
□ PLEASE ADD 3 for GOLD FLASH over NICKEL
- SNAP-LOCK AND SPACER CLIPS: COPPER ALLOY;
min. 200µm TIN over 80µm NICKEL
PCB-HOLE: ø3,1 ± 0,1mm; PCB-THICKNESS: 1,6mm
- COLLARS: COPPER ALLOY; min. 200µm over 80µm NICKEL
- P.C.B. HOLE DRILLINGS ON SHEET 2
- CONNECTOR IS PART MARKED: 16-00218 □ CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

				tolerance		dim. in mm																				
rev.	description	date	name	date	name																					
a	Original			01.10.14	Henneboel	<table border="1"> <tr> <td>scale:</td> <td>2:1 (5:1)</td> </tr> <tr> <td>material:</td> <td>SEE NOTES</td> </tr> <tr> <td colspan="2">title:</td> </tr> <tr> <td colspan="2">D-SUB FEMALE</td> </tr> <tr> <td colspan="2">50pos. SOLDER PIN STRAIGHT</td> </tr> <tr> <td colspan="2">with snap-lock and spacer clip</td> </tr> <tr> <td colspan="2">dwg no:</td> </tr> <tr> <td colspan="2">16K1A3543</td> </tr> <tr> <td colspan="2">part no:</td> </tr> <tr> <td colspan="2">16-00218 □ (see note 3)</td> </tr> </table>	scale:	2:1 (5:1)	material:	SEE NOTES	title:		D-SUB FEMALE		50pos. SOLDER PIN STRAIGHT		with snap-lock and spacer clip		dwg no:		16K1A3543		part no:		16-00218 □ (see note 3)	
scale:	2:1 (5:1)																									
material:	SEE NOTES																									
title:																										
D-SUB FEMALE																										
50pos. SOLDER PIN STRAIGHT																										
with snap-lock and spacer clip																										
dwg no:																										
16K1A3543																										
part no:																										
16-00218 □ (see note 3)																										
				01.10.14	Strakerjahn																					

CONEC®

DIN-A3
sh: 1/2

