



NOTES:

- METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
- INSULATORS: PBT GF UL 94 V-0, BLACK
- CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.):
 - PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
 - PLEASE ADD B for 20µin HARD GOLD over min. 50µin NICKEL
 - PLEASE ADD C for 30µin HARD GOLD over min. 50µin NICKEL
- FIXING PLATE: PBT GF UL 94 V-0; BLACK
- CONNECTOR IS PART MARKED: **163□11249X CONEC ABC** (see part 3)

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm	scale: 2:1 (5:1)		
				material: SEE NOTES		
	drawn	06.02.14	Henneboel	title: D-SUB MALE 90° 37pos. SOLDER PIN ANGLED 0.370inch with fixing-plate		
	appd.	06.02.14	Lehmenkühler			
	norm					
	d-old					
a	Original		dwg no: 16K1A3396		DIN-A3 sh: 1/2	
rev.	description	date			part no: 163□11249X (see note 3)	

