


**SAFETY ISOLATING TRANSFORMER**

POWER : 2VA  
 INPUT VOLTAGE : 230V  
 FREQUENCY : 50/60Hz  
 NOMINAL OUTPUT VOLTAGE : 9V

INHERENTLY SHORT CIRCUIT PROOF TRANSFORMER  
 IPOO  
 UL94V0  
 OPERATING TEMPERATURE : -25°C to 70°C  
 STORAGE TEMPERATURE : -25°C to 85°C  
 INSULATION CLASS (IEC85) : B  
 INHERENT PROTECTION

STANDARDS :  
 UL506 (File E111078)  
 CSA 22-2 (File E111078)  
 UL1585 (File E240724)  
 VDE (File Ref:1398300)  
 EN60950 (File Ref:1398300)  
 EN61558-1 (File Ref:1398300)  
 EN61558-2-6 (File Ref:1398300)  
 CE

<b>44122</b> 230V 50/60Hz (1-5) 9V 2VA (7-9) ta 70/B	 Class II not wet Class III wet EN 60950 www.myrra.com	N°31
---	--	------



Finition:		Tolérance générale:	
Finition:		General tolerance:	
Ech: 1:1	Matière:		
	Material:		
Dessiné par: ROUSSEL.Ch	Date: 27/05/2004	Visa:	J.P.M.

Rev	Date	Modification	Dessiné	Visa

**DATA SHEET 44122**  
**EI 30x15.5**

	22 Allée du Clos des Charmes Z.A. Les Portes de la Forêt 77090 COLLEGIEN Tel : 01-60-37-55-55 Fax : 01-60-17-12-00	DS44122
--	--	---------