

ISOLATING TRANSFORMER

POWER : 4VA
 INPUT VOLTAGE : 2x115V
 FREQUENCY : 50/60Hz
 NOMINAL OUTPUT VOLTAGE : 2x18V

NON SHORT CIRCUIT PROOF TRANSFORMER


IPOO
 UL94HB
 OPERATING TEMPERATURE : -25°C to 70°C
 STORAGE TEMPERATURE : -25°C to 85°C
 INSULATION CLASS (IEC85) : B
 REQUIRED PROTECTION : 125mA FUSE ON EACH SECONDARY

STANDARDS :

UL506 (File E111078)
 CSA 22-2 (File E111078)

CE

CONFORM TO :
 EN61558-1
 EN61558-2-4



Rev	Date	Modification	Dessiné	Visa
D				
C				
B				
A				

Finition:		Tolérance générale:	
Finition:		General tolerance:	
Ech: 1:1	Matière:		
	Material:		
Dessiné par: ROUSSEL.Ch	Date: 19/09/2005	Visa: J.P.M.	
DATA SHEET 45023			
UI 30x7.5			
		22 Allée du Clos des Charmes Z.A. Les Portes de la Forêt 77090 COLLEGIEN Tel : 01-60-37-55-55 Fax : 01-60-17-12-00	
		DS45023	