

BK200A


Old Product Number: HHR200A

Nickel Metal Hydride Battery [N: Standard]

Dimensions



Typical charge characteristics



Specifications

Diameter	17.0 +0 / -0.7 mm
Height	43.0 +0 / -1.5 mm
Approximate Weight	32 g

Nominal Voltage		1.2 V
Discharge Capacity	Average ^{*2}	2040 mAh
	Rated (min.)	2000 mAh
Approx. Internal impedance at 1000Hz at charged state.		20 mΩ
Charge	Standard	200 mA X 16 hrs.
	Rapid ^{*3}	1700 mA X 1.4 hrs.
Ambient Temperature	Charge	Standard: 0 °C to 45 °C Rapid: 0 °C to 40 °C
	Discharge	-10 °C to 65 °C
Storage	<1 year	-20 °C to 35 °C
	<6 months	-20 °C to 45 °C
	<1 month	-20 °C to 55 °C
	<1 week	-20 °C to 65 °C

*1 After charging at 0.1 It for 16 hours, discharging at 0.2 It.



*2 For reference only.

*3 Need specially designed control system. Please contact Panasonic Energy for details.

Attention

Battery performance and cycle life are strongly affected by how they are used. In order to maximize battery safety, please consult Panasonic Energy when determining charge/discharge specs, warning label contents and unit design.

Typical discharge characteristics



Panasonic Energy Co., Ltd.

<https://industrial.panasonic.com/ww/products/pt/nickel-metal>

As of April, 2022. This data in this document is for descriptive purposes only and is not intended to make or imply any guarantee or warranty. The contents of this product information are subject to change without notice.

