



公差等级/General Tolerances(mm)	
0	>3
~	~
3	6
~	10
+0.12	+0.18
+0.22	+0.26
+0.31	+0.37
+0.57	+0.80
+0.93	+1.05
+1.15	+1.60
+2.20	+2.50
±Z	±Z

4	Screws	Steel	Ni Plated
3	Cage	Copper alloy	Sn Plated
2	Pin Header	Copper	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准 /UL Standard:		B	C
额定电压/电涌/Rated Voltage(V)/Current(A)		150/6	/
IEC 标准 /IEC Standard:		/	/
过压类别 /Overvoltage Category/特类等		/	III/2
级 /Pollution Degree		/	/
额定电压/电涌/Rated Voltage(V)/Current(A)		/	130/8
工额电压 /Withstanding Voltage(V/Min)		/	AC1250
螺丝扭矩/Torque Tightening(N·m/Lb.in)		M1.6	0.15/1.29
线径范围(硬线和软线) /Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)		0.5~1.0	26~18
间距/Pitch(mm) /线距范围/Poles		5.00	N=02~12P
剥线长度/Stripping length(mm)			4.5
使用温度范围 /Operating Temperature(°C)			-40~+105
符合RoHS环保要求 /Conform to RoHS			Yes
标准颜色编号 /Standard color number:			/
PANTONE /RAL			/

MATERIAL:

MAT NO.:

STATUS:

APPD: Li GL 2020.06.15

CHKD: Moo J 2020.06.15

DRT:Wgng LX 2020.06.15

NAME:  
**DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**

DG308-2.54-XXP-1Y-00A(H)

DRAWING NO.: DG308-C01

TYPE: CUSTOMER DRAWING

SCALE: 5:1

REV	ECN	DESCRIPTION	DRT	DATE
1				
2				
3				
4				

SIZE	SIZE: A4	TYPE	SCALE	REV	SHEET
mm	inch	CUSTOMER DRAWING	5:1	T0	1/1