

Chip Ferrite Bead BLM15□□□□SN1□ Reference Specification

1.Scope

This Reference specification applies to Chip Ferrite Bead BLM15_SN series.

2.Part Numbering

(ex.) BL M 15 AG 100 S N 1 D

(1) (2) (3) (4) (5) (6) (7) (8) (9)

(1)Product ID (2)Type (3)Dimension(LxW) (4)Characteristics (5)Typical Impedance at 100MHz

(6)Performance (7)Category (8)Numbers of Circuit (9)Packaging(D:Taping / B:Bulk)

3.Rating

| Customer Part Number | MURATA Part Number | Impedance (Ω) (at 100MHz, Under Standard Testing Condition) | | Rated Current (mA) | DC Resistance (Ω max.) | | Remark | |
|----------------------|----------------------------------|---|------|--------------------|--------------------------------|----------------------|-----------------|----------------------------|
| | | Typical | | | Initial Values | Values After Testing | | |
| | BLM15AG100SN1D BLM15AG100SN1B | 5~15 | 10 | 1000 | 0.025 | 0.05 | For general use | |
| | BLM15AG700SN1D BLM15AG700SN1B | 40~100 | 70 | 600 | 0.15 | 0.20 | | |
| | BLM15AG121SN1D BLM15AG121SN1B | 120±25% | 120 | 550 | 0.19 | 0.29 | | |
| | BLM15AG221SN1D BLM15AG221SN1B | 220±25% | 220 | 450 | 0.29 | 0.39 | | |
| | BLM15AG601SN1D BLM15AG601SN1B | 600±25% | 600 | 300 | 0.52 | 0.62 | | |
| | BLM15AG102SN1D BLM15AG102SN1B | 1000±25% | 1000 | 300 | 0.65 | 0.75 | | |
| | BLM15AX100SN1D BLM15AX100SN1B | 5~15 | 10 | 1740 | 0.015 | 0.025 | | |
| | BLM15AX300SN1D BLM15AX300SN1B | 30±25% | 30 | 1100 | 0.06 | 0.11 | | |
| | BLM15AX700SN1D BLM15AX700SN1B | 70±25% | 70 | 780 | 0.10 | 0.15 | | |
| | BLM15AX121SN1D BLM15AX121SN1B | 120±25% | 120 | 700 | 0.13 | 0.18 | | |
| | BLM15AX221SN1D BLM15AX221SN1B | 220±25% | 220 | 600 | 0.18 | 0.23 | | |
| | BLM15AX601SN1D BLM15AX601SN1B | 600±25% | 600 | 500 | 0.34 | 0.39 | | |
| | BLM15AX102SN1D BLM15AX102SN1B | 1000±25% | 1000 | 350 | 0.49 | 0.54 | | |
| | BLM15BA050SN1D BLM15BA050SN1B | 5±25% | 5 | 300 | 0.10 | 0.15 | | For high speed signal line |
| | BLM15BB050SN1D BLM15BB050SN1B | 5±25% | 5 | 500 | 0.08 | 0.15 | | |
| | BLM15BA100SN1D BLM15BA100SN1B | 10±25% | 10 | 300 | 0.20 | 0.25 | | |
| | BLM15BB100SN1D BLM15BB100SN1B | 10±25% | 10 | 300 | 0.10 | 0.15 | | |
| | BLM15BA220SN1D BLM15BA220SN1B | 22±25% | 22 | 300 | 0.30 | 0.35 | | |
| | BLM15BB220SN1D BLM15BB220SN1B | 22±25% | 22 | 300 | 0.20 | 0.30 | | |
| | BLM15BA330SN1D BLM15BA330SN1B | 33±25% | 33 | 300 | 0.40 | 0.45 | | |


| Customer Part Number | MURATA Part Number | Impedance (Ω) (at 100MHz, Under Standard Testing Condition) | | (Note) Rated Current (mA) | DC Resistance (Ω max.) | | Remark |
|----------------------|--------------------|---|---------|------------------------------|--------------------------------|----------------------|----------------------------|
| | | | Typical | | Initial Values | Values After Testing | |
| | BLM15BA470SN1D | 47 \pm 25% | 47 | 200 | 0.60 | 0.65 | For high speed signal line |
| | BLM15BA470SN1B | | | | | | |
| | BLM15BB470SN1D | 47 \pm 25% | 47 | 300 | 0.35 | 0.45 | |
| | BLM15BB470SN1B | | | | | | |
| | BLM15BA750SN1D | 75 \pm 25% | 75 | 200 | 0.80 | 0.85 | |
| | BLM15BA750SN1B | | | | | | |
| | BLM15BB750SN1D | 75 \pm 25% | 75 | 300 | 0.40 | 0.50 | |
| | BLM15BB750SN1B | | | | | | |
| | BLM15BD750SN1D | 75 \pm 25% | 75 | 300 | 0.20 | 0.30 | |
| | BLM15BD750SN1B | | | | | | |
| | BLM15BB121SN1D | 120 \pm 25% | 120 | 300 | 0.55 | 0.65 | |
| | BLM15BB121SN1B | | | | | | |
| | BLM15BD121SN1D | 120 \pm 25% | 120 | 300 | 0.30 | 0.4 | |
| | BLM15BD121SN1B | | | | | | |
| | BLM15BB221SN1D | 220 \pm 25% | 220 | 200 | 0.80 | 0.90 | |
| | BLM15BB221SN1B | | | | | | |
| | BLM15BC121SN1D | 120 \pm 25% | 120 | 350 | 0.45 | 0.50 | |
| | BLM15BC121SN1B | | | | | | |
| | BLM15BD221SN1D | 220 \pm 25% | 220 | 300 | 0.40 | 0.50 | |
| | BLM15BD221SN1B | | | | | | |
| | BLM15BD471SN1D | 470 \pm 25% | 470 | 200 | 0.60 | 0.70 | |
| | BLM15BD471SN1B | | | | | | |
| | BLM15BC241SN1D | 240 \pm 25% | 240 | 250 | 0.70 | 0.75 | |
| | BLM15BC241SN1B | | | | | | |
| | BLM15BD601SN1D | 600 \pm 25% | 600 | 200 | 0.65 | 0.75 | |
| | BLM15BD601SN1B | | | | | | |
| | BLM15BD102SN1D | 1000 \pm 25% | 1000 | 200 | 0.90 | 1.0 | |
| | BLM15BD102SN1B | | | | | | |
| | BLM15BD182SN1D | 1800 \pm 25% | 1800 | 100 | 1.4 | 1.5 | |
| | BLM15BD182SN1B | | | | | | |
| | BLM15BX750SN1D | 75 \pm 25% | 75 | 600 | 0.15 | 0.20 | |
| | BLM15BX750SN1B | | | | | | |
| | BLM15BX121SN1D | 120 \pm 25% | 120 | 600 | 0.17 | 0.22 | |
| | BLM15BX121SN1B | | | | | | |
| | BLM15BX221SN1D | 220 \pm 25% | 220 | 450 | 0.27 | 0.32 | |
| | BLM15BX221SN1B | | | | | | |
| | BLM15BX471SN1D | 470 \pm 25% | 470 | 350 | 0.41 | 0.46 | |
| | BLM15BX471SN1B | | | | | | |
| | BLM15BX601SN1D | 600 \pm 25% | 600 | 350 | 0.46 | 0.51 | |
| | BLM15BX601SN1B | | | | | | |
| | BLM15BX102SN1D | 1000 \pm 25% | 1000 | 300 | 0.65 | 0.75 | |
| | BLM15BX102SN1B | | | | | | |
| | BLM15BX182SN1D | 1800 \pm 25% | 1800 | 250 | 0.90 | 1.0 | |
| | BLM15BX182SN1B | | | | | | |

| Customer Part Number | MURATA Part Number | Impedance (Ω) (at 100MHz, Under Standard Testing Condition) | | (Note) Rated Current (mA) | | DC Resistance (Ω max.) | | Remark |
|----------------------|----------------------------------|---|-----|---------------------------|----------|--------------------------------|----------------------|-------------------|
| | | Typical | | at 85°C | at 125°C | Initial Values | Values After Testing | |
| | BLM15PG100SN1D BLM15PG100SN1B | 5~15 | 10 | 1000 | | 0.025 | 0.05 | For DC power line |
| | BLM15PD300SN1D BLM15PD300SN1B | 30±25% | 30 | 2200*1 | 1400*1 | 0.035 | 0.05 | |
| | BLM15PD600SN1D BLM15PD600SN1B | 60±25% | 60 | 1700*1 | 1100*1 | 0.06 | 0.075 | |
| | BLM15PD800SN1D BLM15PD800SN1B | 80±25% | 80 | 1500*1 | 1000*1 | 0.07 | 0.085 | |
| | BLM15PD121SN1D BLM15PD121SN1B | 120±25% | 120 | 1300*1 | 900*1 | 0.09 | 0.105 | |
| | BLM15PX330SN1D BLM15PX330SN1B | 33±25% | 33 | 3000*1 | 1700*1 | 0.022 | 0.037 | |
| | BLM15PX600SN1D BLM15PX600SN1B | 60±25% | 60 | 2500*1 | 1400*1 | 0.032 | 0.047 | |
| | BLM15PX800SN1D BLM15PX800SN1B | 80±25% | 80 | 2300*1 | 1300*1 | 0.038 | 0.053 | |
| | BLM15PX121SN1D BLM15PX121SN1B | 120±25% | 120 | 2000*1 | 1100*1 | 0.055 | 0.070 | |
| | BLM15PX181SN1D BLM15PX181SN1B | 180±25% | 180 | 1500*1 | 800*1 | 0.090 | 0.105 | |
| | BLM15PX221SN1D BLM15PX221SN1B | 220±25% | 220 | 1400*1 | 800*1 | 0.10 | 0.115 | |
| | BLM15PX331SN1D BLM15PX331SN1B | 330±25% | 330 | 1200*1 | 700*1 | 0.15 | 0.165 | |
| | BLM15PX471SN1D BLM15PX471SN1B | 470±25% | 470 | 1000*1 | 600*1 | 0.20 | 0.22 | |
| | BLM15PX601SN1D BLM15PX601SN1B | 600±25% | 600 | 900*1 | 500*1 | 0.23 | 0.25 | |


■ Operating Temperature : -55°C to +125°C

■ Storage Temperature : -55°C to +125°C


(Note) As for the Rated current marked with *1, Rated Current is derated as right figure depending on the operating temperature.



4.Style and Dimensions



■ Equivalent Circuit



(Resistance element becomes dominant at high frequencies.)

■ Unit Mass(Typical value)
0.001g

5.Marking

No marking.

6.Standard Testing Conditions

< Unless otherwise specified >

Temperature : Ordinary Temp. (15 °C to 35 °C)

Humidity : Ordinary Humidity (25%(RH) to 85%(RH))

< In case of doubt >

Temperature : 20°C±2 °C



Humidity : 60%(RH) to 70%(RH)

Atmospheric pressure : 86kPa to 106kPa

7.Specifications**7-1.Electrical Performance**

| No. | Item | Specification | Test Method |
|-------|---------------|---------------|---|
| 7-1-1 | Impedance | Meet item 3. | Measuring Frequency : 100MHz±1MHz Measuring Equipment : Agilent4291A or the equivalent Test Fixture : Agilent16192A or the equivalent |
| 7-1-2 | DC Resistance | Meet item 3. | Measuring Equipment : Digital multi meter |

7-2.Mechanical Performance

| No. | Item | Specification | Test Method | | | | | | |
|------------------------------|------------------------------|---|--|-----------|------------------------------|-------------|---------------|--------------|--|
| 7-2-1 | Appearance And Dimensions | Meet item 4. | Visual Inspection and measured with Slide Calipers. | | | | | | |
| 7-2-2 | Bonding Strength | Meet Table 1. <u>Table 1</u> <table border="1" style="margin-left: 20px;"> <tr> <td>Appearance</td> <td>No damage</td> </tr> <tr> <td>Impedance Change (at 100MHz)</td> <td>Within ±30%</td> </tr> <tr> <td>DC Resistance</td> <td>Meet item 3.</td> </tr> </table> | Appearance | No damage | Impedance Change (at 100MHz) | Within ±30% | DC Resistance | Meet item 3. | It shall be soldered on the substrate. Applying Force(F) : 5N Applying Time : 5s±1s Applying Direction: Parallel to the substrate.  |
| Appearance | No damage | | | | | | | | |
| Impedance Change (at 100MHz) | Within ±30% | | | | | | | | |
| DC Resistance | Meet item 3. | | | | | | | | |
| 7-2-3 | Bending Strength | | It shall be soldered on the substrate. Substrate: Glass-epoxy 100mm×40mm×0.8mm Deflection : 2.0mm Speed of Applying Force : 0.5mm/s Keeping Time : 30s  | | | | | | |
| 7-2-4 | Vibration | | It shall be soldered on the substrate. Oscillation Frequency : 10Hz to 55Hz to 10Hz for 1 min Total Amplitude : 1.5mm Testing Time : A period of 2 hours in each of 3 mutually perpendicular directions. (Total 6 h) | | | | | | |
| 7-2-5 | Resistance to Soldering Heat | | Pre-Heating : 150°C±10°C, 60s~90s Solder : Sn-3.0Ag-0.5Cu Solder Temperature : 270°C±5°C Immersion Time : 10s±0.5s Immersion and emersion rates : 25mm/s Then measured after exposure in the room condition for 48h±4h. | | | | | | |
| 7-2-6 | Drop | Products shall be no failure after tested. | It shall be dropped on concrete or steel board. Method : free fall Height : 75cm Attitude from which the product is dropped : 3 direction The number of times : 3 times for each direction (Total 9 times) | | | | | | |

| No. | Item | Specification | Test Method |
|-------|---------------|---|---|
| 7-2-7 | Solderability | The electrodes shall be at least 95% covered with new solder coating. | Flux : Ethanol solution of rosin,25(wt)% Pre-Heating : 150°C±10°C, 60s~90s Solder : Sn-3.0Ag-0.5Cu Solder Temperature : 240°C±5°C Immersion Time : 3s±1s Immersion and emersion rates : 25mm/s |


7-3.Environmental Performance

It shall be soldered on the substrate.

| No. | Item | Specification | Test Method | | | | | | |
|------------------------------|---------------------------------------|--|---|-----------|------------------------------|---------------------------------------|---------------|--------------|---|
| 7-3-1 | Temperature Cycle | Meet Table 1. | 1 cycle : 1 step : -55 °C(+0 °C,-3 °C) / 30min±3min 2 step : Ordinary temp. / 10min to 15min 3 step : +125 °C(+3 °C,-0 °C) / 30min±3min 4 step : Ordinary temp. / 10min to 15min Total of 100 cycles Then measured after exposure in the room condition for 48h±4h. | | | | | | |
| 7-3-2 | Humidity | | Temperature : 40°C±2°C Humidity : 90%RH to 95%RH Time : 1000h(+48h,-0h) Then measured after exposure in the room condition for 48h±4h. | | | | | | |
| 7-3-3 | Heat Life | Meet Table 2. <u>Table 2</u> <table border="1"> <tr> <td>Appearance</td> <td>No damage</td> </tr> <tr> <td>Impedance Change (at 100MHz)</td> <td>Within ±30% (for BLM15PD Within ±40%)</td> </tr> <tr> <td>DC Resistance</td> <td>Meet item 3.</td> </tr> </table> | Appearance | No damage | Impedance Change (at 100MHz) | Within ±30% (for BLM15PD Within ±40%) | DC Resistance | Meet item 3. | Temperature : 125°C±3°C Applying Current : Rated Current(at 125°C) Time : 1000h(+48h,-0h) Then measured after exposure in the room condition for 48h±4h. |
| Appearance | No damage | | | | | | | | |
| Impedance Change (at 100MHz) | Within ±30% (for BLM15PD Within ±40%) | | | | | | | | |
| DC Resistance | Meet item 3. | | | | | | | | |
| 7-3-4 | Cold Resistance | Meet Table 1. | Temperature : -55±2°C Time : 1000h(+48h,-0h) Then measured after exposure in the room condition for 48h±4h. | | | | | | |

8.Specification of Packaging

8-1.Appearance and Dimensions (8mm-wide paper tape)



(1) Taping

Products shall be packaged in the cavity of the base tape of 8mm-wide, 2mm-pitch continuously and sealed by top tape and bottom tape.

(2) Sprocket hole:Sprocket hole shall be located on the right hand side toward the direction of feed.

(3) Spliced point:The base tape and top tape have no spliced point

(4) Cavity:There shall not be burr in the cavity.

(5) Missing components number

Missing components number within 0.1% of the number per reel or 1 pc., whichever is greater, and are not continuous. The specified quantity per reel is kept.

8-2.Tape Strength


(1) Pull Strength

| | |
|-------------|---------|
| Top tape | 5N min. |
| Bottom tape | |

(2) Peeling off force of Cover tape

0.1N to 0.6N (Minimum value is typical.)

*Speed of Peeling off:300mm/min



8-3.Taping Condition

(1) Standard quantity per reel

| | |
|-------------------------|-------------------|
| Quantity per 180mm reel | 10000 pcs. / reel |
|-------------------------|-------------------|

(2) There shall be leader-tape(top tape and empty tape) and trailer- tape(empty tape) as follows.


(3) On paper tape, the top tape and the base tape shall not be adhered at the tip of the empty leader tape for more than 5 pitch.

(4) Marking for reel

The following items shall be marked on a label and the label is stuck on the reel.

(Customer part number, MURATA part number, Inspection number(*1) , RoHS marking(*2) , Quantity, etc)

*1) « Expression of Inspection No. »



(1) Factory Code

(2) Date


First digit : Year / Last digit of year

Second digit : Month / Jan. to Sep. → 1 to 9, Oct. to Dec. → O,N,D

Third, Fourth digit : Day

(3) Serial No.

*2) « Expression of RoHS marking »



(1) RoHS regulation conformity parts.


(2) MURATA classification number

(5) Outside package


These reels shall be packed in the corrugated cardboard package and the following items shall be marked on a label and the label is stuck on the box.

(Customer name, Purchasing order number, Customer part number, MURATA part number, RoHS marking(*2) ,Quantity, etc)

(6)Dimensions of reel and taping(leader-tape, trailer-tape)



8-4. Specification of Outer Case



| Outer Case Dimensions (mm) | | | Standard Reel Quantity in Outer Case (Reel) |
|----------------------------|-----|----|---|
| W | D | H | |
| 186 | 186 | 93 | 5 |

* Above Outer Case size is typical. It depends on a quantity of an order.

9. **Caution**

9-1. Surge current

Excessive surge current (pulse current or rush current) than specified rated current applied to the product may cause a critical failure, such as an open circuit, burnout caused by excessive temperature rise. Please contact us in advance in case of applying the surge current.

9-2.Limitation of Applications

Please contact us before using our products for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property.

- (1)Aircraft equipment
- (2)Aerospace equipment
- (3)Undersea equipment
- (4)Power plant control equipment
- (5)Medical equipment
- (6)Disaster prevention / crime prevention equipment
- (7)Traffic signal equipment
- (8)Transportation equipment (vehicles, trains, ships, etc.)
- (9)Applications of similar complexity and /or reliability requirements to the applications listed in the above


10.Notice

This product is designed for solder mounting.


Please consult us in advance for applying other mounting method such as conductive adhesive.

10-1.Land pattern designing

- Standard land dimensions (Reflow soldering)
- < For BLM15 series (except BLM15P□, BLM15AX type) >



< For BLM15P□, BLM15AX type >



| Rated Current (A) | a | b | c | Land pad thickness and dimension d | | |
|-------------------|-----|------------|-----|------------------------------------|------|------|
| | | | | 18μm | 35μm | 70μm |
| 1.5 Max | 0.4 | 1.2 to 1.4 | 0.5 | 0.5 | 0.5 | 0.5 |
| 2.2 Max | | | | 1.2 | 0.7 | 0.5 |
| 3.0 Max | | | | 2.4 | 1.2 | 0.5 |

(in mm)

*The excessive heat by land pads may cause deterioration at joint of products with substrate.

10-2.Soldering Conditions

Products can be applied to reflow soldering.

(1) Flux,Solder

| | |
|--------|--|
| Flux | Use rosin-based flux, but not highly acidic flux (with chlorine content exceeding 0.2(wt)%.) Do not use water-soluble flux. |
| Solder | Use Sn-3.0Ag-0.5Cu solder Standard thickness of solder paste : 100 μm to 200 μm |

(2) Soldering conditions


- Pre-heating should be in such a way that the temperature difference between solder and ferrite surface is limited to 150°C max. Also cooling into solvent after soldering should be in such a way that the temperature difference is limited to 100°C max.

Insufficient pre-heating may cause cracks on the ferrite, resulting in the deterioration of product quality.

- Standard soldering profile and the limit soldering profile is as follows.

The excessive limit soldering conditions may cause leaching of the electrode and / or resulting in the deterioration of product quality.

(3) Soldering profile



| | Standard Profile | Limit Profile |
|------------------|---------------------|----------------------|
| Pre-heating | 150~180°C , 90s±30s | |
| Heating | above 220°C、30s~60s | above 230°C、60s max. |
| Peak temperature | 245±3°C | 260°C,10s |
| Cycle of reflow | 2 times | 2 times |


10-3. Reworking with soldering iron

- Pre-heating: 150°C, 1 min
- Tip temperature: 350°C max.
- Soldering time : 3(+1,-0) seconds.
- Soldering iron output: 80W max.
- Tip diameter: φ 3mm max.
- Times : 2times max.

Note :Do not directly touch the products with the tip of the soldering iron in order to prevent the crack on the ferrite material due to the thermal shock.

10-4.Solder Volume

Solder shall be used not to be exceed as shown below.



$$\frac{1}{3}T \leq t \leq T$$

(T:Chip thickness)


Accordingly increasing the solder volume, the mechanical stress to product is also increased. Exceeding solder volume may cause the failure of mechanical or electrical performance.

10-5.Attention regarding P.C.B. bending

The following shall be considered when designing and laying out P.C.B.'s.

- (1) P.C.B. shall be designed so that products are not subject to the mechanical stress for board warpage.


<Products direction>



Products shall be located in the sideways direction (Length:a<b) to the mechanical stress.

- (2)Products location on P.C.B. separation.

Products (A,B,C,D) shall be located carefully so that products are not subject to the mechanical stress due to warping the board. Because they may be subjected the mechanical stress in order of $A > C > B \cong D$.



10-6.Mounting density

Add special attention to radiating heat of products when mounting the inductor near the products with heating. The excessive heat by other products may cause deterioration at joint of this product with substrate.

10-7.Operating Environment

Do not use this product under the following environmental conditions, on deterioration of the Insulation Resistance of the Ferrite material and/or corrosion of Inner Electrode may result from the use.

- (1) in the corrodible atmosphere (acidic gases, alkaline gases, chlorine, sulfur gases, organic gases and etc.)
- (2) in the atmosphere where liquid such as organic solvent, may splash on the products.
- (3) in the atmosphere where the temperature / humidity changes rapidly and it is easy to dew.

10-8.Resin coating

The impedance value may change and/or it may affect on the product's performance due to high cure-stress of resin to be used for coating / molding products. So please pay your careful attention when you select resin. In prior to use, please make the reliability evaluation with the product mounted in your application set.

10-9.Cleaning Conditions

Products shall be cleaned on the following conditions.


- (1)Cleaning temperature shall be limited to 60°C max. (40°C max. for IPA.)
- (2)Ultrasonic cleaning shall comply with the following conditions, avoiding the resonance phenomenon at the mounted products and P.C.B.
Power:20W/ℓ max. Frequency:28kHz to 40kHz Time:5 min max.
- (3)Cleaner
 - 1.Alternative cleaner
 - Isopropyl alcohol (IPA)
 - 2.Aqueous agent
 - PINE ALPHA ST-100S
- (4)There shall be no residual flux and residual cleaner after cleaning.
In the case of using aqueous agent, products shall be dried completely after rinse with de-ionized water in order to remove the cleaner.
- (5)Other cleaning
Please contact us.

10-10. Handling of a substrate


After mounting products on a substrate, do not apply any stress to the product caused by bending or twisting to the substrate when cropping the substrate, inserting and removing a connector from the substrate or tightening screw to the substrate.

Excessive mechanical stress may cause cracking in the product.

Bending



Twisting



10-11.Storage Conditions

(1)Storage period

Use the products within 6 months after delivered.

Solderability should be checked if this period is exceeded.

(2)Storage conditions

- Products should be stored in the warehouse on the following conditions.

Temperature : -10°C to 40°C

Humidity : 15% to 85% relative humidity

No rapid change on temperature and humidity

- Don't keep products in corrosive gases such as sulfur, chlorine gas or acid, or it may cause oxidization of electrode, resulting in poor solderability.
- Products should be stored on the palette for the prevention of the influence from humidity, dust and so on.
- Products should be stored in the warehouse without heat shock, vibration, direct sunlight and so on.
- Products should be stored under the airtight packaged condition.

(3)Delivery

Care should be taken when transporting or handling product to avoid excessive vibration or mechanical shock.

11. Note

(1)Please make sure that your product has been evaluated in view of your specifications with our product being mounted to your product.

(2)You are requested not to use our product deviating from the reference specifications.

(3)The contents of this reference specification are subject to change without advance notice. Please approve our product specifications or transact the approval sheet for product specifications before ordering.