






Quick Interchangeable Crimping Tool Terminal Installation Kit

HT-K6A02



1. HT-435FM **PAT. P.**

Quick interchangeable ratchet crimper (frame only).

2. HT-42C

Dimension AWG 20-18 / 16-14 / 12-10
 DIN 0.5-1 / 1.5-2.5 / 4-6 mm²
Cable type Non-insulated Terminal or Open Barrel Terminal



3. HT-42C3

Dimension AWG 24-30 / 18-22
 DIN 0.25-0.05 / 1.0-0.35 mm²
Cable type D-Sub Terminal



4. HT-42E2

Dimension AWG 20 / 18 / 17 / 16 / 14 / 12 / 10 / 8 / 6
 DIN 0.5/0.75/1.0/1.5/2.5 / 4 / 6 / 10 / 16 mm²
Cable type Pin Terminal Insulated or Non-insulated Ferrules



5. HT-42H

Dimension AWG 20-18 / 16-14 / 12-10
 DIN 0.5-1 / 1.5-2.5 / 4-6 mm²
Cable type Insulated Terminal



6. HT-42N

Dimension AWG 18-16 / 14 / 12-10 / 8
 DIN 0.75-1.5 / 2.5 / 4-6 / 10 mm²
 JIS 0.9-1.4 / 2.0 / 3.5-5.5 / 8 mm²
Cable type Non-insulated Terminal

