

N-Channel Power MOSFET

600V, 24A, 165mΩ

FEATURES

- Super-Junction technology
- High performance, small $R_{DS(ON)} * Q_g$ figure of merit (FOM)
- High ruggedness performance
- 100% UIS & R_g tested
- High commutation performance
- ROHS Compliant
- Halogen-free according to IEC 61249-2-21

KEY PERFORMANCE PARAMETERS		
PARAMETER	VALUE	UNIT
V_{DS}	600	V
$R_{DS(on)}$ (max)	165	mΩ
Q_g	44	nC

APPLICATIONS



- Power Supply
- AC/DC LED Lighting



✓
RoHS
COMPLIANT

HALOGEN
FREE

ITO-220



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	LIMIT	UNIT
Drain-Source Voltage	V_{DS}	600	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current (Note 1)	I_D	24	A
		15	A
Pulsed Drain Current (Note 2)	I_{DM}	72	A
Total Power Dissipation @ $T_C = 25^\circ\text{C}$	P_D	89	W
Single Pulse Avalanche Energy (Note 3)	E_{AS}	450	mJ
Single Pulse Avalanche Current (Note 3)	I_{AS}	4.2	A
Operating Junction and Storage Temperature Range	T_J, T_{STG}	- 55 to +150	°C

THERMAL PERFORMANCE

PARAMETER	SYMBOL	LIMIT	UNIT
Junction to Case Thermal Resistance	R_{eJC}	1.4	°C/W
Junction to Ambient Thermal Resistance	R_{eJA}	60	°C/W

Note: R_{eJA} is the sum of the junction-to-case and case-to-ambient thermal resistances. R_{eJA} is guaranteed by design while R_{eJA} is determined by the user's board design.

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)						
PARAMETER	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNIT
Static <small>(Note 4)</small>						
Drain-Source Breakdown Voltage	$V_{GS} = 0\text{V}$, $I_D = 1\text{mA}$	BV_{DSS}	600	--	--	V
Gate Threshold Voltage	$V_{DS} = V_{GS}$, $I_D = 1\text{mA}$	$V_{GS(\text{TH})}$	3	3.9	5	V
Gate Body Leakage	$V_{GS} = \pm 20\text{V}$, $V_{DS} = 0\text{V}$	I_{GSS}	--	--	± 100	nA
Zero Gate Voltage Drain Current	$V_{DS} = 600\text{V}$, $V_{GS} = 0\text{V}$	I_{DSS}	--	--	100	μA
Drain-Source On-State Resistance	$V_{GS} = 10\text{V}$, $I_D = 11.3\text{A}$	$R_{DS(\text{on})}$	--	150	165	$\text{m}\Omega$
Dynamic <small>(Note 5)</small>						
Total Gate Charge	$V_{DS} = 300\text{V}$, $I_D = 24\text{A}$, $V_{GS} = 10\text{V}$	Q_g	--	44	--	nC
Gate-Source Charge		Q_{gs}	--	13	--	
Gate-Drain Charge		Q_{gd}	--	18	--	
Input Capacitance	$V_{DS} = 300\text{V}$, $V_{GS} = 0\text{V}$, $f = 1.0\text{MHz}$	C_{iss}	--	1857	--	pF
Output Capacitance		C_{oss}	--	53	--	
Reverse Transfer Capacitance		C_{rss}	--	13	--	
Gate Resistance	$f = 1.0\text{MHz}$	R_g	--	1.6	3.2	Ω
Switching <small>(Note 6)</small>						
Turn-On Delay Time	$V_{DD} = 300\text{V}$, $R_G = 10\Omega$, $I_D = 15\text{A}$, $V_{GS} = 10\text{V}$	$t_{d(on)}$	--	30	--	ns
Turn-On Rise Time		t_r	--	50	--	
Turn-Off Delay Time		$t_{d(off)}$	--	60	--	
Turn-Off Fall Time		t_f	--	12	--	
Source-Drain Diode <small>(Note 4)</small>						
Body-Diode Continuous Forward Current		I_S	--	--	20	A
Body-Diode Pulsed Current		I_{SM}	--	--	60	A
Forward Voltage	$I_S = 20\text{A}$, $V_{GS} = 0\text{V}$	V_{SD}	--	0.9	1.4	V
Reverse Recovery Time	$I_S = 20\text{A}$ $dI_F/dt = 100\text{A}/\mu\text{s}$	t_{rr}	--	410	--	ns
Reverse Recovery Charge		Q_{rr}	--	8.5	--	μC

Notes:

1. Current limited by package.
2. Pulse width limited by the maximum junction temperature.
3. $L = 50\text{mH}$, $I_{AS} = 4.2\text{A}$, $V_{DD} = 50\text{V}$, $R_G = 25\Omega$, Starting $T_J = 25^\circ\text{C}$
4. Pulse test: $PW \leq 300\mu\text{s}$, duty cycle $\leq 2\%$.
5. For DESIGN AID ONLY, not subject to production testing.
6. Switching time is essentially independent of operating temperature.


ORDERING INFORMATION

ORDERING CODE	PACKAGE	PACKING
TSM60NC165CI C0G	ITO-220	50pcs / Tube


CHARACTERISTICS CURVES

($T_c = 25^\circ\text{C}$ unless otherwise noted)


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Gate-Source Voltage vs. Gate Charge



On-Resistance vs. Junction Temperature








On-Resistance vs. Gate-Source Voltage




CHARACTERISTICS CURVES

($T_C = 25^\circ\text{C}$ unless otherwise noted)



PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

ITO-220



NOTES: UNLESS OTHERWISE SPECIFIED


1. ALL DIMENSIONS ARE IN MILLIMETERS.

2. DIMENSIONING AND TOLERANCING
PER ASME Y14.5M-1994.

3. PACKAGE OUTLINE REFERENCE:
EIAJ ED-7500A-1, SC-91.

4 MOLDED PLASTIC BODY DIMENSIONS DO NOT INCLUDE MOLD FLASH. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREME OF THE PLASTIC BODY.

5. DWG NO. REF: HQ2SD07-ITO220-072 REV A.



MARKING DIAGRAM

P/N	= MARKING CODE
Y	= YEAR CODE
WW	= WEEK CODE (01 ~ 52)
L	= LOT CODE (1~9, A~Z)
F	= FACTORY CODE

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.