


Rating	16A 125V AC/10A 250V AC 10(4)A 250V AC
Contact resistance	50mΩ Max
Insulation resistance	DC 500V 100MΩ Min
Dielectric strength	AC 1500V 1 minute
Cut-out	

FEATURES

- * MATERIAL: Frame is nylon (UL flame: 94V-2). Terminals are silver plated brass.
- * Illuminated actuators are molded in PC, available with red, amber, green, blue and white colors.
- * Snap-in mounting, easy to install switch into panel.
- * Watertight cover is optional.



Ordering number instruction

R13-244 -

FUNCTION	TERMINAL
Different position / Illuminated button (動作特性不同/帶燈)	0 2 .187" SQ

Different position / Illuminated button (動作特性不同/帶燈)

<p>B</p> <p>4P DPST (NEON) 125VAC 33KΩ / 250VAC 150KΩ</p>	<p>C B</p> <p>6P DPDT (NEON) 125VAC 33KΩ / 250VAC 150KΩ</p>	<p>D B</p> <p>6P DPDT (NEON) 125VAC 33KΩ / 250VAC 150KΩ</p>
--	--	--

ROCKER

A		A8	
B		B8	
C/CB		C8	
D/DB		DB	
G		DB8	
H			

Different position (動作特性不同)

<p>A</p> <p>4P DPST</p>	<p>C</p> <p>6P DPDT</p>	<p>D</p> <p>6P DPDT</p>
--------------------------------	--------------------------------	--------------------------------

Momentary (彈回)

<p>G</p> <p>6P DPDT</p>	<p>H</p> <p>6P DPDT</p>	<p>I</p> <p>6P DPDT</p>
--------------------------------	--------------------------------	--------------------------------

Watertight (防水)

<p>A 8</p> <p>4P DPST (NEON) 125VAC 33KΩ / 250VAC 150KΩ</p>	<p>B 8</p> <p>6P DPDT (NEON) 125VAC 33KΩ / 250VAC 150KΩ</p>	<p>C 8</p> <p>6P DPDT (NEON) 125VAC 33KΩ / 250VAC 150KΩ</p>	<p>C B 8</p> <p>6P DPDT (NEON) 125VAC 33KΩ / 250VAC 150KΩ</p>
--	--	--	--

D 8

6P DPDT

D B 8

6P DPDT (NEON)
125VAC 33KΩ / 250VAC 150KΩ

