







SENSITIVE GATE SCR

<p>TO-92 (FS01xxxA)</p>  <p>SOT-223 (FS01xxxN)</p>  <p>SOT23-3L (FS01xxxL)</p>  	<p>On-State Current 0.8 Amp</p> <p>Gate Trigger Current < 200 μA</p> <p>Off-Satate Voltage 400 V \div 600 V</p>
	<p>FEATURES</p> <ul style="list-style-type: none"> • Glass/passivated die junctions • Low current SCR • Low thermal resistance • High surge current capability • Low forward voltage drop • Solder dip 260 °C, 10s • Component in accordance to RoHS 2011/65/EU and WEEE 2002/96/EC • Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C <p style="text-align: right;">   RoHS COMPLIANT </p>
	<p>MECHANICAL DATA</p> <ul style="list-style-type: none"> • Case: TO92/ sot-223/ sot23-3L. Epoxy meets UL 94V-0 flammability rating. • Polarity: As marked on the body. • Terminals: Matte tin plated leads, solderable per MIL-STD-750 Method 2026, J-STD-002 and JESD22-B102. Consumer grade, meets JESD 201 class 1A whisker test.
	<p>TYPICAL APPLICATIONS</p> <p>Thanks to highly sensitive triggering levels, the FS011xxxx SCR is suitable for all applications where available gate current is limited, such as ground fault circuit interruptors, pilot circuits in sold state relays, stand-by mode power supplies, smoke and alarm detectors.</p>


Maximun Ratings and Electrical Characteristics at 25 °C

SYMBOL	PARAMETER	CONDITIONS	Value	Unit
$I_{T(RMS)}$	RMS On-State Current	180 ° Conduction Angel, $T_c = 115$ °C	0.8	A
$I_{T(AV)}$	Average On-State Current	180 ° Conduction Angel, $T_c = 115$ °C	0.5	A
I_{TSM}	Non-repetitive On-State Current	Half Cycle, 60 Hz	8	A
I_{TSM}	Non-repetitive On-State Current	Half Cycle, 50 Hz	7	A
I^2t	Fusing Current	$t_p = 10$ ms, Half Cycle	0.24	A ² s
I_{GM}	Peak Gate Current	20 μ s max. $T_j = 125$ °C	1	A
$P_{G(AV)}$	Average Gate Power Dissipation	$T_j = 125$ °C	0.1	W
T_j	Operating Temperature		(-40 to + 125)	°C
T_{stg}	Storage Temperature		(-40 to + 150)	°C
T_{std}	Soldering Temperature	10s max.	260	°C

SYMBOL	PARAMETER	CONDITIONS	Voltage		Unit
			D	M	
V_{DRM} V_{RRM}	Repetitive Peak Off State Voltage	$R_{GK} = 1k\Omega$	400	600	V

Electrical Characteristics at Tamb = 25 °C

SYMBOL	PARAMETER	CONDITIONS	SENSITIVITY					Unit	
			01	02	03	04	18		
I_{GT}	Gate Trigger Current	$V_D = 12 V_{DC}, R_L = 140\Omega, T_j = 25^\circ C$	MIN	1		20	15	0.5	μA
			MAX	20	200	200	50	5	
V_{GT}	Gate Trigger Voltage	$V_D = 12 V_{DC}, R_L = 140\Omega, T_j = 25^\circ C$	MAX	0.8					V
V_{GD}	Gate Non Trigger Voltage	$V_D = V_{DRM}, R_L = 3.3k\Omega, R_{GK} = 220\Omega, T_j = 125^\circ C$	MIN	0.1					V
V_{RGM}	Reverse Gate Voltage	$I_{RG} = 10\mu A$	MIN	8					V
I_H	Holding Current	$I_T = 50 mA, R_{GK} = 1k\Omega, T_j = 25^\circ C$	MAX	5					mA
I_L	Latching Current	$I_G = 1 mA, R_{GK} = 1k\Omega$	MAX	6					mA
dV / dt	Critical Rate of Voltage Rise	$V_D = 0.67 \times V_{DRM}, R_{GK} = 1k\Omega, T_j = 125^\circ C$	MIN	80	75	80	80	80	V/ μs
dl / dt	Critical Rate of Current Rise	$I_G = 2 \times I_{GT}, tr \leq 100ns, f = 60Hz, T_j = 125^\circ C$	MIN	50					A/ μs
V_{TM}	On-State Voltage	at $I_T = 1.6 Amp, tp = 380 \mu s, T_j = 25^\circ C$	MAX	1.95					V
V_{IO}	Threshold Voltage	$T_j = 125^\circ C$	MAX	0.95					V
r_d	Dynamic resistance	$T_j = 125^\circ C$	MAX	600					m Ω
I_{DRM} / I_{RRM}	Off-State Leakage Current	$V_D = V_{DRM}, R_{GK} = 1k\Omega, T_j = 125^\circ C$ $V_R = V_{RRM}, T_j = 25^\circ C$	MIN	100 1					μA μA
$R_{th(j-c)}$	Thermal Resistance Junction-Case for DC	TO-92	80					$^\circ C/W$	
		SOT-223	30					$^\circ C/W$	
$R_{th(j-a)}$	Thermal Resistance Junction-Amb for DC	Mounted on recommed Pad Layout	400					$^\circ C/W$	
		SOT-23-3L							
		TO-92	150					$^\circ C/W$	
		$S = 5 cm^2$	60					$^\circ C/W$	

Part Number Information


SENSITIVE GATE SCR

Ordering information


PREFERRED P/N	PACKAGE CODE	DELIVERY MODE	BASE QUANTITY	UNIT WEIGHT (g)
FS0102DA 00AM	AM	AMMO	2,000	0.2
FS0102DA 00BU	BU	BULK	10,000	0,2

PREFERRED P/N	PACKAGE CODE	DELIVERY MODE	BASE QUANTITY	UNIT WEIGHT (g)
FS0102DN 00RB	RB	REEL	2,500	0.116

PREFERRED P/N	PACKAGE CODE	DELIVERY MODE	BASE QUANTITY	UNIT WEIGHT (g)
FS0102DL 00RB	RB	REEL	3,000	0.01


Package Outline Dimensions: (mm) TO92

TO-92 (BU)




REF.	DIMENSIONS		
	Milimeters		
	Min.	Typ.	Max.
A	0.90	1.20	1.50
B	4.40	4.60	4.80
C	2.34	2.54	2.74
D	1.07	1.27	1.47
E	4.40	4.60	4.80
F	12.70	14.10	15.50
G	3.40	3.60	3.86
H	1.30	1.50	1.70
a	0.38	0.44	0.51
b	0.33	0.41	0.51

TO-92 (AMMO)




REF.	DIMENSIONS		
	Milimeters		
	Min.	Typ.	Max.
A	0.90	1.20	1.50
B	4.40	4.60	4.80
C	4.96	5.08	5.20
D	2.42	2.54	2.66
E	4.40	4.60	4.80
F	12.30	13.70	15.50
G	3.40	3.60	3.86
H	1.30	1.50	1.70
a	0.38	0.44	0.51
b	0.33	0.41	0.51

Package Outline Dimensions: (mm) TO-261AA (SOT-223)



Package Outline Dimensions: (mm) SOT23-3L



Rating and Characteristics (Ta 25 °C unless otherwise noted)

Fig. 1: Maximum average power dissipation versus average on-state current




Fig. 2: Average and D.C. on-state current versus ambient temperature




Fig. 3: Relative variation of thermal impedance junction to ambient versus pulse duration




Fig. 4: Relative variation of gate trigger, holding and latching current versus junction temperature (Typical values)




Fig. 5: Relative variation of holding current versus gate-cathode resistance (Typical values)




Fig. 6: Relative variation of dV/dt immunity versus gate-cathode resistance (Typical values)




Fig. 7: Relative variation of dV/dt immunity versus gate-cathode capacitance (Typical values)




Fig. 8: Non repetitive surge peak on-state current versus number of cycles




Fig. 9: Non repetitive surge peak on-state current and corresponding value of $I^2 t$





Fig.10 On-state characteristics (Maximum values)



Revision History

DATE	REVISION	DESCRIPTION OF CHANGES
18-Feb-2014	0	Original Data Sheet
10-Dec-2015	1	Updated Ordering Information

Disclaimer

All product, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.

Fagor Electrónica, S. Coop., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Fagor"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Fagor makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Fagor disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Fagor's knowledge of typical requirements that are often placed on Fagor products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Fagor's terms and conditions or purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Fagor products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Fagor product could result in personal injury or death. Customers using or selling Fagor products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Fagor and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Fagor or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Fagor personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Fagor. Products names and markings noted herein may be trademarks of their respective owners.