


This drawing may not be used, reproduced or made available in any form without written or prior written approval.

The supplier acknowledges that, with the acceptance of this drawing, he is a participant in manufacturing the illustrated part in accordance with the drawing's requirements. He is responsible for the correct interpretation of the drawing and for the correct execution of the manufacturing process. He is not responsible for any deviations from the drawing's requirements.

Technische Daten/ technical data	:	Akkupack/ batterypack
Chemie/ chemistry	:	Lithium Ion
Zellenzahl/ no. of cells	:	8 Zellen/ cells INR18650 M26 LG ; 4S2P
Kapazität/ capacity	:	nom. 5200mAh discharge at 0.2C min. 5000mAh discharge at 0.2C to:20°C; EV(Discharge End Voltage): 2.75V per cell
Innenwiderstand/ impedance	:	< 180m0hm (battery and safetyboard)
Nominalspannung/ nominal voltage	:	14.4V
Standard Ladespannung/ standard charge voltage	:	16.8V±1%
Standard Entladespannung/ standard discharge voltage	:	11V
Nominaler Ladestrom/ nominal charge current	:	0.5C
Maximaler Ladestrom/ maximum charge current	:	1C
Ladeendstrom/ charge end current	:	0.01C recommended
Maximaler Entladestrom/ maximum discharge current	:	4000mA (limited by safetyboard)
Anwendungstemperaturbereich/ ambient temperature range	:	0°C...+45°C charge -20°C...+60°C discharge -20°C...+20°C storage max. 1 year -20°C...+45°C storage max. 3months
Selbstentladung/ self discharge	:	≤ 5% / month at20°C ≤ 10% / month at30°C ≤ 20% / month at40°C
Standards/	:	UN 3480, Subsection 38.3 All cells and batterypacks type tested according to UN manual of test and criteria subsection 38.3



Technische Daten/ technical data	:	Sicherheitsschaltung/ safety board
Überladeschutzspannung/ over charge voltage detection	:	4.325V±75mV per cell
Wiedereinschaltspannung/ over charge release voltage	:	4.15V±50mV per cell
Entladeabschaltspannung/ over discharge detection voltage	:	2.4V±80mV per cell
Wiedereinschaltspannung/ over discharge release voltage	:	3V±100mV per cell
Nominaler Lade/Entladestrom/ nominal operating current	:	4A
Entlade Abschaltstrom/ discharge cut off current	:	15A± 5A
Kurzschlusschutz/ short circuit protection	:	gegen äußeren Kurzschluss/ against external short circuit
Temperaturschalter/ temperature switch	:	---
MOSFET	:	im Pluszweig/ in positive path
Rückstellkriterium/ release condition	:	Last trennen, Aktiv nach Anladen/ cut load, release after charging up
Nettogewicht/ net weight	:	370g
Leiterplattenmaterial/ pcb material	:	FR4
Standards	:	CE

Part Number	SAP Description
2447-3035-03	Li-Ion-14.4V-5200mAh-4S2P-M26
2447-3035-203	Li-Ion-14.4V-5200mAh-4S2P-M26/UK

Verwendungsbereich/Application range für Anfrage/for inquiry AN-IS-2013-00427				Zul. Abweichung/ Allowable deviation	Oberfläche/ Surface	Maßstab/Scale (DIN A2): 1:1	Gewicht/Weight
				Allgemeintoleranz DIN ISO 2768-m		Werkstoff/Work material, Modell-Nr.	
				2019	Datum/Date	Zeichnungsname/Drawing name	
				Zeichner/ Drawn by	25.01.	MSt	Li-Ion Battery 14.4V 5200mAh with safetyboard
							Zeichnungsnummer/Drawing number
							Artikelnummer/Part number
V1	part number overview added	15.04.19	DS				2447-3035-XXX
V0	----	XX.XX.XX	XX				1
Version		Änderung/Change		Datum/Date		Ursprung/Origin Proj. IS-2013-00427	Ersatz für/Replaced by
						Ersatz durch/Replaced through	