OSRAM SFH 203 P

Datasheet

Discontinued

Published by ams-OSRAM AG
Tobelbader Strasse 30, 8141 Premstaetten, Austria
Phone +43 3136 500-0
ams-osram.com
© All rights reserved

OSRAM

Radial T1 3/4

SFH 203 P

Silicon PIN Photodiode



Applications

- Access control & security
- Appliances & tools

Features

- ESD: 2 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 2)
- Wavelength range ($S_{10\%}$) 400 nm to 1100 nm
- Short switching time (typ. 5 ns)
- 5 mm LED plastic package

Discontinued

Ordering Information

Type	Photocurrent [1)] E_v = 1000 lx; Std. Light A; V_R = 5 V I_P	Photocurrent typ. E_v = 1000 lx; Std. Light A; V_R = 5 V I_P	Ordering Code
SFH 203 P	≥ 5.5 µA	9.5 µA	Q62702P0942

Discontinued

Maximum Ratings

T_A = 25 °C

Parameter	Symbol		Values
Operating Temperature	T_{op}	min. max.	-40 °C 100 °C
Storage temperature	T_{stg}	min. max.	-40 °C 100 °C
Reverse voltage	V_R	max.	20 V
Reverse voltage t ≤ 2 min; T_A = 25 °C	V_R	max.	50 V
Total power dissipation	P_{tot}	max.	150 mW
ESD withstand voltage acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 2)	V_{ESD}	max.	2 kV

Discontinued

Characteristics


T_A = 25 °C

Parameter	Symbol		Values
Wavelength of max sensitivity	$\lambda_{S\ max}$	typ.	850 nm
Spectral range of sensitivity	$\lambda_{10\%}$	typ.	400 ... 1100 nm
Radiant sensitive area	A	typ.	1.00 mm²
Dimensions of active chip area	L x W	typ.	1 x 1 mm x mm
Half angle	φ	typ.	75 °
Dark current V_R = 20 V	I_R	typ. max.	1 nA 5 nA
Spectral sensitivity of the chip λ = 850 nm	S_λ	typ.	0.62 A / W
Quantum yield of the chip λ = 850 nm	η	typ.	0.90 Electrons / Photon
Open-circuit voltage E_v = 1000 lx; Std. Light A; V_R = 0 V	V_O	min. typ.	300 mV 350 mV
Short-circuit current E_v = 1000 lx; Std. Light A; V_R = 0 V	I_{SC}	typ.	9.3 µA
Rise time V_R = 20 V; R_L = 50 Ω; λ = 850 nm	t_r	typ.	0.005 µs
Fall time V_R = 20 V; R_L = 50 Ω; λ = 850 nm	t_f	typ.	0.005 µs
Forward voltage I_F = 100 mA; E = 0	V_F	typ.	1.3 V
Capacitance V_R = 0 V; f = 1 MHz; E = 0	C_0	typ.	11 pF
Temperature coefficient of voltage	TC_V	typ.	-2.6 mV / K
Temperature coefficient of short-circuit current Std. Light A	TC_I	typ.	0.18 % / K
Noise equivalent power V_R = 20 V; λ = 850 nm	NEP	typ.	0.029 pW / $Hz^{1/2}$
Detection limit V_R = 20 V; λ = 850 nm	D*	typ.	3.5e12 cm x $Hz^{1/2}$ / W

Discontinued


Relative Spectral Sensitivity [2], [3]

$S_{rel} = f(\lambda)$



Directional Characteristics [2], [3]


$S_{rel} = f(\varphi)$



Discontinued


Photocurrent/Open-Circuit Voltage [2], [3]

I_P (V_R = 5 V) / V_O = f (E_v)




Dark Current [2], [3]

I_R = f (V_R); E = 0



Capacitance [2], [3]


C = f (V_R); f = 1MHz; E = 0; T_A = 25°C



Discontinued


Dark Current [2)]

$I_R = f(T_A)$; E = 0; V_R = 20 V



Discontinued

Dimensional Drawing [4)]




Further Information:

Approximate Weight: 268.0 mg

Package marking: Cathode

Discontinued

Recommended Solder Pad [4)]




E062.3010.188-01

Pad 1: anode

Discontinued

TTW Soldering

IEC-61760-1 TTW



Notes

Subcomponents of this device contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize device exposure to aggressive substances during storage, production, and use. Devices that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

Packing information is available on the internet (online product catalog).

For further application related information please visit https://ams-osram.com/support/application-notes

Discontinued

Disclaimer

Attention please!

The information describes the type of component and shall not be considered as assured characteristics.
Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.
For information on the types in question please contact our Sales Organization.
If printed or downloaded, please find the latest version on our website.

Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Product and functional safety devices/applications or medical devices/applications

Our components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.
Our products are not qualified at module and system level for such application.

In case buyer – or customer supplied by buyer – considers using our components in product safety devices/ applications or medical devices/applications, buyer and/or customer has to inform our local sales partner immediately and we and buyer and /or customer will analyze and coordinate the customer-specific request between us and buyer and/or customer.

Discontinued

Glossary

1) **Photocurrent:** The photocurrent values are measured (by irradiating the devices with a homogenous light source and applying a voltage to the device) with a tolerance of ±11 %.

2) **Typical Values:** Due to the special conditions of the manufacturing processes of semiconductor devices, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.

3) **Testing temperature:** TA = 25°C (unless otherwise specified)

4) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with ±0.1 and dimensions are specified in mm.

Discontinued

Revision History

Version	Date	Change
1.4	2022-08-11	Applications New Layout
1.5	2026-03-18	Discontinued

Discontinued

Discontinued

EU RoHS and China RoHS compliant product
此产品符合欧盟 RoHS 指令的要求；
按照中国的相关法规和标准，
不含有毒有害物质或元素。

Published by ams-OSRAM AG
Tobelbader Strasse 30, 8141 Premstaetten, Austria
Phone +43 3136 500-0
ams-osram.com
© All rights reserved