

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : KONTAKT LS  
 UFI : SY3X-5872-500X-055W  
 Product code : BDS001671AE  
 Type of product : Detergent  
 Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Main use category : Professional use  
 Use of the substance/mixture : Cleaners - Precision

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

CRC Industries Europe B.V.  
 Touwslagerstraat 1  
 9240 Zele  
 Belgium  
 T +32(0)52/45.60.11, F +32(0)52/45.00.34  
[hse@crcind.com](mailto:hse@crcind.com), [www.crcind.com](http://www.crcind.com)

#### 1.4. Emergency telephone number

Emergency number : +32(0)52/45.60.11  
 Office hours: 9-17h CET

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229  
 Skin corrosion/irritation, Category 2 H315  
 Serious eye damage/eye irritation, Category 2 H319  
 Specific target organ toxicity – Single exposure, Category 3, Narcosis H336  
 Aspiration hazard, Category 1 H304  
 Hazardous to the aquatic environment – Chronic Hazard, Category 2 H411  
 Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Contains :

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane;propan-2-ol; isopropyl alcohol; isopropanol

# KONTAKT LS

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	: H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H315 - Causes skin irritation. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours/spray. P271 - Use only outdoors or in a well-ventilated area. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EC-No.: 921-024-6 REACH-no: 01-2119475514-35	25 – 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
ethanol; ethyl alcohol substance with national workplace exposure limit(s) (BE)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-43	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319
propan-2-ol; isopropyl alcohol; isopropanol substance with national workplace exposure limit(s) (BE)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558-25	10 – 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Carbon dioxide (CO <sub>2</sub> ) substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 124-38-9	5 – 10	Press. Gas (Comp.), H280

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
ethanol; ethyl alcohol	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-43	(50 ≤ C < 100) Eye Irrit. 2; H319

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

# KONTAKT LS

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Seek medical attention if irritation develops.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Seek medical attention if irritation develops.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately. Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: Risk of lung oedema.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	: During fire, gases hazardous to health may be formed.

#### 5.3. Advice for firefighters

Firefighting instructions	: Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Protective equipment	: Wear appropriate protective equipment and clothing during clean-up.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

##### For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Ventilate area.

# KONTAKT LS

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

### 6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
- Methods for cleaning up : Mechanically recover the product. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual contamination.
- Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For disposal of contaminated materials refer to section 13 : "Disposal considerations".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety procedures.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Keep container closed when not in use.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### National occupational exposure and biological limit values

Carbon dioxide (CO <sub>2</sub> ) (124-38-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Carbon dioxide
IOEL TWA	9000 mg/m <sup>3</sup>
	5000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Belgium - Occupational Exposure Limits	
Local name	Carbone (dioxyde de) # Koolstofdioxide
OEL TWA	9131 mg/m <sup>3</sup>
	5000 ppm
OEL STEL	54784 mg/m <sup>3</sup>

# KONTAKT LS

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Carbon dioxide (CO <sub>2</sub> ) (124-38-9)	
	30000 ppm
Remark	A: la mention "A" signifie que l'agent libère un gaz ou une vapeur qui n'ont en eux-mêmes aucun effet physiologique mais peuvent diminuer le taux d'oxygène dans l'air. Lorsque le taux d'oxygène descend en dessous de 17-18 % (vol/vol) le manque d'oxygène provoque des suffocations qu'aucun symptôme préalable n'annonce. # A: de vermelding "A" betekent dat dit agens gas of damp vrijgeeft dat of die op zich geen fysiologische werking heeft, maar het zuurstofgehalte in de lucht verlaagt. Wanneer het zuurstofgehalte daalt onder de 17-18 % (vol/vol), veroorzaakt het zuurstoftekort verstikking, die zich manifesteert zonder dat er een waarschuwing aan voorafgaat.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
Belgium - Occupational Exposure Limits	
Local name	Alcool isopropylique # Isopropylalcohol
OEL TWA	500 mg/m <sup>3</sup> 200 ppm
OEL STEL	1000 mg/m <sup>3</sup> 400 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023

ethanol; ethyl alcohol (64-17-5)	
Belgium - Occupational Exposure Limits	
Local name	Alcool éthylique # Ethanol
OEL TWA	1907 mg/m <sup>3</sup> 1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023

### DNEL and PNEC

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	773 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2035 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	699 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	608 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	699 mg/kg bodyweight/day
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	888 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	500 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	26 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	89 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	319 mg/kg bodyweight/day

# KONTAKT LS

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)</b>	
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	140,9 mg/l
PNEC aqua (marine water)	140,9 mg/l
PNEC aqua (intermittent, freshwater)	140,9 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	552 mg/kg dwt
PNEC sediment (marine water)	552 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	28 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	160 mg/kg food
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	2251 mg/l
<b>ethanol; ethyl alcohol (64-17-5)</b>	
<b>DNEL/DMEL (Workers)</b>	
Acute - local effects, inhalation	1900 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	343 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	950 mg/m <sup>3</sup>
<b>DNEL/DMEL (General population)</b>	
Acute - local effects, inhalation	950 mg/m <sup>3</sup>
Long-term - systemic effects, oral	87 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	114 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	206 mg/kg bodyweight/day
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0,96 mg/l
PNEC aqua (marine water)	0,79 mg/l
PNEC aqua (intermittent, freshwater)	2,75 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	3,6 mg/kg dwt
PNEC sediment (marine water)	2,9 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	0,63 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	0,72 g/kg food
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	580 mg/l

# KONTAKT LS

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2. Exposure controls

#### Appropriate engineering controls

##### Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

#### Personal protection equipment

##### Personal protective equipment symbol(s):



#### Eye and face protection

##### Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

#### Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Neoprene gloves are recommended.

#### Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: AX

#### Thermal hazards

##### Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

#### Environmental exposure controls

##### Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Appearance	: CO2 propelled liquid.
Odour	: Solvent.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Extremely flammable aerosol.
Explosive properties	: Pressurised container: May burst if heated.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: -35 °C (closed cup)
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: Not available
pH	: Not applicable
Viscosity, kinematic	: < 5 mm <sup>2</sup> /s at 40 °C

# KONTAKT LS

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 0,74 g/cm <sup>3</sup> at 20 °C
Relative density	: 0,74 at 20 °C
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### Information with regard to physical hazard classes

% of flammable ingredients : 75 – 100 %

#### Other safety characteristics

VOC content : 704 g/l  
Additional information : For aerosols data for the product without propellant.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity (oral)** : Not classified (Based on available data, the classification criteria are not met)  
**Acute toxicity (dermal)** : Not classified (Based on available data, the classification criteria are not met)  
**Acute toxicity (inhalation)** : Not classified (Based on available data, the classification criteria are not met)

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

LD50 oral rat	5841 mg/kg
LD50 dermal rat	2800 – 3100 mg/kg bodyweight
LC50 Inhalation - Rat	> 25,2 mg/l/4h

#### propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)

LD50 oral rat	5840 mg/kg bodyweight
---------------	-----------------------

#### ethanol; ethyl alcohol (64-17-5)

LD50 oral rat	15010 mg/kg bodyweight
---------------	------------------------

# KONTAKT LS

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>ethanol; ethyl alcohol (64-17-5)</b>	
LD50 dermal	15800 mg/kg bodyweight
LC50 Inhalation - Rat (Vapours)	> 116,9 mg/l/4h

<b>Skin corrosion/irritation</b>	: Causes skin irritation. pH: Not applicable
<b>Serious eye damage/irritation</b>	: Causes serious eye irritation. pH: Not applicable
<b>Respiratory or skin sensitisation</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Germ cell mutagenicity</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Carcinogenicity</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>Reproductive toxicity</b>	: Not classified (Based on available data, the classification criteria are not met)
<b>STOT-single exposure</b>	: May cause drowsiness or dizziness.

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
STOT-single exposure	May cause drowsiness or dizziness.

<b>propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

<b>STOT-repeated exposure</b>	: Not classified (Based on available data, the classification criteria are not met)
-------------------------------	-------------------------------------------------------------------------------------

<b>ethanol; ethyl alcohol (64-17-5)</b>	
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight

<b>Aspiration hazard</b>	: May be fatal if swallowed and enters airways.
--------------------------	-------------------------------------------------

<b>KONTAKT LS</b>	
Vaporizer	Aerosol
Viscosity, kinematic	< 5 mm <sup>2</sup> /s at 40 °C

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
Viscosity, kinematic	0,7 mm <sup>2</sup> /s at 20 °C

### 11.2. Information on other hazards

#### Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties	: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %
------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
LC50 - Fish [1]	11,4 mg/l
EC50 - Crustacea [1]	3 mg/l
EC50 72h - Algae [1]	10 mg/l
LOEC (chronic)	0,32 mg/l

# KONTAKT LS

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
NOEC (chronic)	0,17 mg/l
NOEC chronic fish	2,04 mg/l
NOEC chronic crustacea	1 mg/l

<b>propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)</b>	
LC50 - Fish [1]	10000 mg/l
LC50 - Fish [2]	9640 mg/l

<b>ethanol; ethyl alcohol (64-17-5)</b>	
LC50 - Fish [1]	14,2 g/l
EC50 - Other aquatic organisms [1]	5012 mg/l
ErC50 algae	275 mg/l
NOEC (chronic)	9,6 mg/l

### 12.2. Persistence and degradability

<b>KONTAKT LS</b>	
Persistence and degradability	Not established. No data is available on the degradability of this product.

### 12.3. Bioaccumulative potential

<b>KONTAKT LS</b>	
Partition coefficient n-octanol/water (Log Kow)	Not applicable

<b>Carbon dioxide (CO2) (124-38-9)</b>	
Partition coefficient n-octanol/water (Log Pow)	0,83

<b>ethanol; ethyl alcohol (64-17-5)</b>	
Partition coefficient n-octanol/water (Log Pow)	-0,32

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

<b>KONTAKT LS</b>	
Results of PBT assessment	Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

### 12.7. Other adverse effects

<b>KONTAKT LS</b>	
Other information	No other effects known
Global warming potential (GWP)	0.05 (Fluorinated greenhouse gases - (EC) No 2024/573)

# KONTAKT LS

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
European List of Waste (LoW, EC 2000/532) : According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used.

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
<b>Transport document description</b>				
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-D EmS-No. (Spillage): S-U	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

#### 14.6. Special precautions for user

##### Overland transport

Classification code (ADR) : 5F  
Special provisions (ADR) : 190, 327, 344, 625  
Limited quantities (ADR) : 1I  
Excepted quantities (ADR) : E0  
Packing instructions (ADR) : P207, LP200  
Special packing provisions (ADR) : PP87, RR6, L2  
Mixed packing provisions (ADR) : MP9  
Transport category (ADR) : 2  
Special provisions for carriage - Packages (ADR) : V14  
Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12  
Special provisions for carriage - Operation (ADR) : S2

# KONTAKT LS

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Tunnel restriction code (ADR) : D

### Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Limited quantities (IMDG) : SP277  
Excepted quantities (IMDG) : E0  
Packing instructions (IMDG) : P207, LP200  
Special packing provisions (IMDG) : PP87, L2  
Stowage category (IMDG) : None  
Stowage and handling (IMDG) : SW1, SW22  
Segregation (IMDG) : SG69

### Air transport

PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 203  
PCA max net quantity (IATA) : 75kg  
CAO packing instructions (IATA) : 203  
CAO max net quantity (IATA) : 150kg  
Special provisions (IATA) : A145, A167, A802  
ERG code (IATA) : 10L

### Inland waterway transport

Classification code (ADN) : 5F  
Special provisions (ADN) : 190, 327, 344, 625  
Limited quantities (ADN) : 1 L  
Excepted quantities (ADN) : E0  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01, VE04  
Number of blue cones/lights (ADN) : 1

### Rail transport

Classification code (RID) : 5F  
Special provisions (RID) : 190, 327, 344, 625  
Limited quantities (RID) : 1L  
Excepted quantities (RID) : E0  
Packing instructions (RID) : P207, LP200  
Special packing provisions (RID) : PP87, RR6, L2  
Mixed packing provisions (RID) : MP9  
Transport category (RID) : 2  
Special provisions for carriage – Packages (RID) : W14  
Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW12  
Colis express (express parcels) (RID) : CE2  
Hazard identification number (RID) : 23

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

# KONTAKT LS

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

### VOC Directive (2004/42)

VOC content : 704 g/l

### Detergent Regulation (648/2004)

Labelling of contents	
Component	%
aliphatic hydrocarbons	≥30%

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods

# KONTAKT LS

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

# KONTAKT LS

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

---

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.