

SUNON

SPECIFICATION FOR APPROVAL FOR REFERENCE

CUSTOMER :
DESCRIPTION : EC 225 CENTRIFUGAL FAN
DIMENSION : 270x270x119 MM
SUNON MODEL : CBAP222BC-1000U-OJ9
MOTOR MODEL : CMP2060G(Y)
SUNON SEQ NO :
REV : 1
ISSUE DATE : 2026.08.26
APPROVED BY CUSTOMER :

Preliminary Data Sheet is for reference only, final specification might be changed according to design verification (or mass production) data. Specifications are subject to change without notice.

APPROVED BY	TSETA	CHECKED BY	LIYONNG	DESIGNED BY	Howard
-------------	-------	------------	---------	-------------	--------

SUNONWEALTH ELECTRIC MACHINE INDUSTRY CO., LTD.

NO.30, LN. 296, XINYA RD., QIANZHEN DIST., KAOHSIUNG CITY 80673, TAIWAN

TEL: +886-7-8135888 FAX: +886 7 213 5125

1. SCOPE

THIS SPECIFICATION DEFINES THE ELECTRICAL AND MECHANICAL CHARACTERISTICS OF THE EC CENTRIFUGAL FAN.

2. CHARACTERISTICS

ITEM	DESCRIPTION
NOMINAL VOLTAGE	1~ 230 VAC 50/60HZ
RATED VOLTAGE	1~ 200 - 240 VAC
RATED POWER	71W @ FREE AIR
MAX. LOAD POWER	85W
SPEED CONTROL	PWM RS485 (MODBUS-RTU) VOLTAGE CONTROL(0-10 VDC)
RATED SPEED	2460RPM
MAX. AIRFLOW	582 CFM 989 m ³ /h
MAX. STATIC PRESSURE	1.49 inch-H ₂ O 370 Pa
INSULATION CLASS	F
PROTECTION CLASS	1
INGRESS PROTECTION	IP55
LIFE EXPECTANCY	60,000 HOURS AT 40 °C WITH 15~65% RH
DIRECTION OF ROTATION	CLOCKWISE VIEWED FROM BLADE SIDE
EMC	EN61000-6-2 , EN61000-6-3
SAFETY	CSA C22.2 N0.77 ; UL 1004-7 + 60730-1 ; EN 60335-1 ; CCC GB12350 (IN PROCESS)

3. MECHANICAL

3.1	BEARING SYSTEM	:	BALL BEARING SYSTEM
3.2	FRAME	:	NA
3.3	FAN GUARD	:	NA
3.4	SUPPORT BRACKET	:	PLASTIC
3.5	SUPPORT PLATE	:	PLASTIC
3.6	INLET NOZZLE	:	PLASTIC
3.7	IMPELLER	:	PA66+25%GF
3.8	ELECTRONICS HOUSING	:	DIE-CAST ALUMINUM
3.9	IMPELLER BALANCE GRADE	:	G6.3 PER ISO 1940-1:2003(E)
3.10	WEIGHT	:	1.9 KG (REF.)


4. ENVIRONMENTAL

4.1	OPERATING TEMPERATURE RANGE	:	-25 TO + 60 DEGREE C
4.2	STORAGE TEMPERATURE RANGE	:	-40 TO + 80 DEGREE C

5. PROTECTION

- ☒ AUTOMATIC RESTART
- ☒ SOFT START
- ☒ OVER TEMPERATURE PROTECTION
- ☒ OVER LOAD PROTECTION
- ☒ OVER VOLTAGE PROTECTION
- ☒ LOCKED ROTOR PROTECTION

6. AIR FLOW & STATIC PRESSURE CURVE



MEASURE DATA:

Index	Static pressure		Air volume		Speed	Power	Current	Lp
	Pa	in-H ₂ O	m ³ /h	CFM	RPM	W	A	dB(A)
1	0	0.00	989	582	2460	71	0.31	70.6
2	191	0.77	745	438	2460	85	0.36	
3	322	1.29	496	292	2460	82	0.36	
4	370	1.49	248	146	2460	72	0.31	
5	0	0.00	792	466	1970	36	0.16	65.8
6	122	0.49	597	351	1970	43	0.19	
7	206	0.83	396	233	1970	42	0.18	
8	237	0.95	199	117	1970	37	0.16	
9	0	0.00	595	350	1477	15	0.07	59.6
10	69	0.28	448	263	1477	18	0.08	
11	116	0.47	298	175	1477	18	0.08	
12	133	0.54	149	88	1477	16	0.07	

TEST CONDITION:

INPUT VOLTAGE: NOMINAL VOLTAGE.

TEMPERATURE: ROOM TEMPERATURE.

MEASURED WITH INLET NOZZLE


NOISE (LP) IS MEASURED AT A DISTANCE OF ONE METER FROM THE INLET SIDE.

NOTE: The airflow and static pressure are measured in accordance with ISO 5801 Category A (using manufacturer's designated test chamber/fixture).

7. DIMENSIONS

SCREW TYPE (PAN HEAD)	TORQUE	SCREW SPEC	
		SIZE	STANDARD
MACHINE SCREW	3~4 Kgf-cm	M4.0	JIS B1111-1974
SELF-TAPPING SCREW	6~8 Kgf-cm	φ5.0	JIS B1122 TYPE 2





NOTE: Above spec is available for customization.



UNIT:mm

ITEM	FUNCTIONS	WIRE TYPE	COLOR
Power	L	UL2517#20AWG	BLUE
	N	UL2517#20AWG	BROWN
	PE	UL2517#20AWG	YELLOW/GREEN
Signal	10 V	UL2517#24AWG	RED
	VIN	UL2517#24AWG	BLUE/WHITE
	FG	UL2517#24AWG	YELLOW
	GND	UL2517#24AWG	BLACK
	RSA	UL2517#24AWG	GRAY
	RSB	UL2517#24AWG	BROWN

8. SPEED SETTING

Full Speed 	Short 10V & VIN Fan will run at full speed.
	Connector 1-10kΩ variable resistor Between 10V with GND and VIN(0-10V/PWM) Vary the variable resistance, to change the 'Vin' voltage (0-10V), then change FAN speed.
Voltage Control B 0-10V DC Source 	Use voltage source supply 0~10V_{DC} voltage DC+ : connector to 1~10V(+) DC- : connector to GND(-)
PWM Control PWM Generator 	PWM duty control PWM amplitude is 10V_{DC}(±5%) Frequency Range is 100Hz-100kHz - PWM duty higher than 15%, fan start up. - PWM duty lower than 5%, fan stop.

9. SIGNAL FUCTION

RS485 control function	RS485 control function –Select the control mode of speed, fixed speed or fixed PWM duty –Speed and power consumption feedback. –Allow multiple FANs control and status patrol. Cable: A MODBUS over Serial Line Cable must be shielded. At one end of each cable its shield must be connected to protective ground.															
Voltage/PWM control	The speed comparison will control level <table><tr><th>Voltage (V)</th><th>PWM (%)</th><th>Speed (RPM) (REF)</th></tr><tr><td>0</td><td>0</td><td>0</td></tr><tr><td>1.0</td><td>10</td><td>100 ± 50 RPM</td></tr><tr><td>5.0</td><td>50</td><td>1280 ± 10%</td></tr><tr><td>9.0</td><td>90</td><td>2460± 5%</td></tr></table>	Voltage (V)	PWM (%)	Speed (RPM) (REF)	0	0	0	1.0	10	100 ± 50 RPM	5.0	50	1280 ± 10%	9.0	90	2460± 5%
Voltage (V)	PWM (%)	Speed (RPM) (REF)														
0	0	0														
1.0	10	100 ± 50 RPM														
5.0	50	1280 ± 10%														
9.0	90	2460± 5%														
FG Signal	$V_{CE(sat)} = 0.7V \text{ MAX.}$ $V_{FG} = 30.0V \text{ MAX.}$ $I_C = 5mA \text{ MAX.}$ $R \geq V_{FG} / I_C$ Frequency generator waveform $V_{FG} \pm 5\%$ 0.7V MAX. RUNNING BLADE LOCKED RUNNING TS T1 T2 OR $N=R.P.M$ 1 PULSE PER REVOLUTION $TS=60/N(SEC)$ $T1=T2=1/2 TS$															

10. VOLTAGE 、PWM VS SPEED CURVE

VOLTAGE(VDC)	0	0.5	1	2	3	4	5	6	7	8	9	10
PWM DUTY(%)	0	5	10	20	30	40	50	60	70	80	90	100
Speed(rpm)	0	0	100	395	690	985	1280	1575	1870	2165	2460	2460



NOTE: It is tested under free air condition. The same spec is not able to apply in static pressure condition