


This drawing may not be copied, reproduced or made available in any form without the written approval of the manufacturer. The supplier acknowledges that, with the acceptance of the drawing, he is a participant in manufacturing the illustrated part in accordance with the drawing's requirements. The manufacturer is not responsible for any damage or loss of data resulting from the use of the drawing. The manufacturer is not responsible for any damage or loss of data resulting from the use of the drawing. The manufacturer is not responsible for any damage or loss of data resulting from the use of the drawing.

Technische Daten/ technical data	:	Akkupack/ batterypack
Chemie/ chemistry	:	Lithium Ion
Zellenzahl/ no. of cells	:	4 Zellen/ cells INR18650 M26 LG ; 4S1P
Kapazität/ capacity	:	nom. 2600mAh discharge at 0.2C min. 2500mAh discharge at 0.2C ta:20°C; EV(Discharge End Voltage): 2.75V per cell
Innenwiderstand/ impedance	:	< 320m0hm (battery and safetyboard)
Nominalspannung/ nominal voltage	:	14.4V
Standard Ladespannung/ standard charge voltage	:	16.8V±1%
Standard Entladespannung/ standard discharge voltage	:	11V
Nominaler Ladestrom/ nominal charge current	:	0.5C
Maximaler Ladestrom/ maximum charge current	:	1C
Ladeendstrom/ charge end current	:	0.01C recommended
Maximaler Entladestrom/ maximum discharge current	:	4000mA (limited by safetyboard)
Anwendungstemperaturbereich/ ambient temperature range	:	0°C...+45°C charge -20°C...+60°C discharge -20°C...+20°C storage max. 1 year -20°C...+45°C storage max. 3months
Selbstentladung/ self discharge	:	≤ 5% / month at20°C ≤ 10% / month at30°C ≤ 20% / month at40°C
Standards/	:	UN 3480, Subsection 38.3 All cells and batterypacks type tested according to UN manual of test and criteria subsection 38.3

Technische Daten/ technical data	:	Sicherheitsschaltung/ safety board
Überladeschutzspannung/ over charge voltage detection	:	4.325V±75mV per cell
Wiedereinschaltspannung/ over charge release voltage	:	4.15V±50mV per cell
Entladeabschaltspannung/ over discharge detection voltage	:	2.4V±80mV per cell
Wiedereinschaltspannung/ over discharge release voltage	:	3V±100mV per cell
Nominaler Lade/Entladestrom/ nominal operating current	:	4A
Entlade Abschaltstrom/ discharge cut off current	:	15A± 5A
Kurzschlusschutz/ short circuit protection	:	gegen äußeren Kurzschluss/ against external short circuit
Temperaturschalter/ temperature switch	:	---
MOSFET	:	im Pluszweig/ in positive path
Rückstellkriterium/ release condition	:	Last trennen, Aktiv nach Anladen/ cut load, release after charging up
Nettogewicht/ net weight	:	190g
Leiterplattenmaterial/ pcb material	:	FR4
Standards	:	CE



Part Number	SAP Description
2447-3032-03	Li-Ion-14.4V-2600mAh-4S1P-M26
2447-3032-203	Li-Ion-14.4V-2600mAh-1S1P/UK

Verwendungsbereich/Application range für Anfrage/for inquiry AN-IS-2013-00424				Zul. Abweichung/ Allowable deviation	Oberfläche/ Surface	Maßstab/Scale (DIN A2): 1:1	Gewicht/Weight
				Allgemeintoleranz DIN ISO 2768-m		Werkstoff/Work material, Modell-Nr.	
				2019	Datum/Date	Name	Zeichnungsname/Drawing name
				Zeichner/ Drawn by	29.01.	MSt	Li-Ion Battery 14.4V 2600mAh with safetyboard
V1	part number overview odder	15.04.19	DS			Zeichnungsnummer/Drawing number	
V0	----	XX.XX.XX	XX			Artikelnummer/Part number	
Version				Datum/Date		Ursprung/Origin Proj. IS-2013-00424	
Änderung/Change						Ersatz für/Replaced by	
						Ersatz durch/Replacement through	